| Swedish LYS-rule classification | | |
|---------------------------------|----------------|--|
| | | |
| Abbreviation | value | Description |
| ID | SF60 | Identification code |
| Boat Type | Sheriff 600 | |
| LYS | 0.90 | LYS classification code |
| UTR | SG- | Indicates ordinary sail wardrobe consisting of Spinnaker and Genoa |
| LÖA | 6.22 m | Overall length, including everything |
| В | 2.30 m | Overall width, including everything |
| DEPL | 1.00 ton | Least allowable displacement |
| Р | 6.80 m | Greatest allowable distance between the inner edge of the upper and lower mast maesuring points. |
| E | 2.70 m | Greatest allowable distance from the after-side of the mast to the inner edge of the booms measuring point. |
| т | 6.30 m | Greatest allowable length of forward jib leech |
| LP | 3.15 m | Greatest allowable distance perpendicular to the forward jib leech |

| J | 2.35 m | Horisontal distance from forward-edge of the mast to the fastening device of the forestay in the deck |
|-----|--------|---|
| SL | 6.20 m | Greatest allowable length of the standing leech of a spinnaker |
| SMW | 4.61 m | The greatest allowable width of the spinnaker |
| SPL | 2.56 m | Greatest allowable distance from the centerline of the forward-edge of the mast to the outermost point of the spinnaker pole when it is placed horisontally, is extended to its maximum and is perpendicular to the centreplane of the hull |