


The FOB HP allows a **25%** weight reduction on some recommended anchor designs.



Patent Guy Royer

Reference Item	Weight kg	Dim. mm		
		A	B	C
354004	4	247	286	505
354006	6	272	346	572
354008	8	312	386	620
354010	10	312	395	650
354012	12	334	416	690
354014	14	358	442	715
354020	20	376	474	850
354024	24	400	495	905
354034	34	472	578	975
354040	40	782	602	1022
354090	90	665	790	1250
354090	90	665	790	1250
354120	120	690	815	1350
354150	150	730	840	1400
354175	175	780	900	1450
354200	200	810	990	1550



FOB SAS

P.O. Box 14
29801 Brest Cedex 09
France

Phone : +33 2 98 02 04 17
Fax : +33 2 98 02 43 48

FOB HP



“The reference”

Certified as High Holding Power anchor by the Bureau Véritas (N° 2785/EO BV).




FOB HP

"The reference"

The FOB HP is certified as "High Holding Power" by the french Bureau Véritas. It has been tested in all weathers and on every type of seabed. The HP's unique design geometry is what gives it its excellent holding power.

- Efficient
- Secure
- Easy to handle



- Oblong hole for easy shackle connection.

Made of galvanized steel or stainless steel (mirror polished).

1 OPTIMUM ANGLE FOR IMMEDIATE GRIP

angle in 30°

2 CROWN DESIGN ENSURES COMPLETE "BURYING"

3 POLYVALENCE

- High efficiency through design geometry.
- Rounded flukes profiles give greater "working" area to increase ground holding.

Chock anchors

To store the anchor on the deck.



- Oblong hole at the end of the shank allows the anchor.